

Table 51 a

Dimensions
GEOCONN

Imperial unit

Pipe Body					Pin	Coupling			Length
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift diameter	Make up loss	Regular Coupling OD	Special Clearance OD	Joint Efficiency	
inch	lbs/ft	inch	inch	inch	inch	inch	inch	%	inch
4 1/2	10.50	0.224	4.052	3.927	3.984	5.000	4.875	119	8.068
	11.60	0.250	4.000	3.875			4.875	107	
	13.50	0.290	3.920	3.795			4.875	93	
	15.10	0.337	3.826	3.701			5.000	103	
5	15.00	0.296	4.408	4.283	4.063	5.563	5.375	92	8.225
	18.00	0.362	4.276	4.151			5.375	77	
5 1/2	15.50	0.275	4.950	4.825	4.125	6.050	5.875	99	8.350
	17.00	0.304	4.892	4.767			5.875	90	
	20.00	0.361	4.778	4.653			5.875	77	
	23.00	0.415	4.670	4.545		6.300	6.050	92	
6 5/8	20.00	0.288	6.424	6.299	4.313	7.390	7.000	96	8.725
7	23.00	0.317	6.366	6.241	4.500	7.875	7.656	139	9.100
	26.00	0.362	6.276	6.151			7.656	122	
	29.00	0.408	6.184	6.059			7.656	109	
	32.00	0.453	6.094	5.969			7.656	99	
	35.00	0.498	6.004	5.879			7.656	91	
	38.00	0.540	5.920	5.795			7.656	84	
7 5/8	26.20	0.328	6.969	6.844	4.688	8.500	8.125	108	9.475
	29.70	0.375	6.875	6.750			8.125	95	
	33.70	0.430	6.765	6.640			8.125	84	
	39.00	0.500	6.625	6.500			8.125	73	
8.625	24.00	0.264	8.097	7.972	4.813	9.625	9.125	134	9.776
	28.00	0.304	8.017	7.892			9.125	117	
	32.00	0.352	7.921	7.796			9.125	102	
	36.00	0.400	7.825	7.700			9.125	90	
9 5/8	36.00	0.352	8.921	8.765	4.813	10.625	10.125	101	9.826
	40.00	0.395	8.835	8.679			10.125	90	
	43.50	0.435	8.755	8.599			10.125	82	
	47.00	0.472	8.681	8.525			10.125	76	
	53.50	0.545	8.535	8.379			10.125	67	
9 7/8	62.80	0.625	9.500	9.344	4.813	10.875	-	-	9.826
10 3/4	45.50	0.400	9.950	9.794	4.813	11.750	11.250	89	9.826
	51.00	0.450	9.850	9.694			11.250	79	
	55.50	0.495	9.760	9.604			11.250	72	
	60.70	0.545	9.660	9.504			11.250	66	
	71.00	0.650	9.450	9.294			11.250	56	
13 3/8	54.50	0.380	12.615	12.459	4.813	14.375	-	-	9.826
	61.00	0.430	12.515	12.359			-	-	
	68.00	0.480	12.415	12.259			-	-	
	72.00	0.514	12.347	12.191			-	-	
16	65.00	0.375	15.250	15.063	4.913	17.000	-	-	9.976
	75.00	0.438	15.124	14.937			-	-	
	84.00	0.495	15.010	14.823			-	-	
	109.00	0.656	14.688	14.501			-	-	
18-5/8	87.50	0.435	17.755	17.568	4.913	20.000	-	-	9.976
	94.50	0.468	17.689	17.502			-	-	
	114.00	0.579	17.467	17.280			-	-	
	126.00	0.636	17.353	17.166			-	-	
20	94.00	0.438	19.124	18.937	4.913	21.000	-	-	9.976
	106.50	0.500	19.000	18.813			-	-	
	133.00	0.635	18.730	18.543			-	-	

Note : Joint Efficiency of Regular Coupling >=100%

Legal Notice

The use of this information is at the reader/user's risk and no warranty is implied or expressed by Metal One Corporation or its parents, subsidiaries or affiliates (herein collectively referred to as "Metal One") with respect to the use of information contained herein. The information provided on this Data Sheet is for informational purposes only, and was prepared by reference to engineering information that is specific to the subject products, without regard to safety-related factors, all of which are the sole responsibility of the operators and users of the subject connectors. Metal One assumes no responsibility for any errors with respect to this information.

Statements regarding the suitability of products for certain types of applications are based on Metal One's knowledge of typical requirements that are often placed on Metal One products in standard well configurations. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

The products described in this Data Sheet are not recommended for use in deep water offshore applications. For more information, please refer to http://www.mto.co.jp/mo-con/_images/top/WebsiteTerms_Active_20333287_1.pdf the contents of which are incorporated by reference into this Data Sheet.