

Table 1 b

SUPERMAX, SUPERMAX2 Dimensions

Metric Unit

Pipe Body					Pin	Coupling			
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift Diameter	Thread length	Standard Coupling OD	Special Clearance OD	Joint Efficiency	Length
mm	Kg/m	mm	mm	mm	mm	mm	mm	%	mm
48.3	4.10	3.68	40.9	38.5	57.3	55.9	N/A		143.5
52.4	4.83	3.96	44.48	42.09	57.3	60.3	N/A		143.5
60.5	6.85	4.83	50.67	48.29	69.3	73.0	68.6	114	167.5
	7.60	5.54	49.3	46.9			68.6	101	
	8.64	6.45	47.4	45.0			69.9	101	
73.0	9.54	5.51	62.0	59.6	70.9	88.9	82.6	112	170.8
	11.47	7.01	59.0	56.6			83.8	101	
	12.81	7.82	57.4	55.0			85.1	102	
88.9	11.47	5.49	77.9	74.8	77.3	108.0	97.8	103	183.5
	13.71	6.45	76.0	72.8			99.1	100	
	15.20	7.34	74.2	71.0			101.6	110	
108.0	14.16	5.74	90.1	86.9	77.3	120.7	111.8	109	188.8
	16.24	6.65	88.3	85.1			113.0	106	
	19.37	8.38	84.8	81.7			115.6	104	
	22.05	9.65	79.8	79.1			118.1	108	
114.3	15.65	5.69	102.9	99.7	83.6	127.0	124.5	109	201.5
	17.28	6.35	101.6	98.4			125.7	110	
	19.00	6.88	100.5	97.4			125.7	102	
	20.12	7.37	99.6	96.4			127.0	106	
	22.50	8.56	97.2	94.0			127.0	100	
127.0	19.37	6.43	114.1	111.0	94.0	141.3	136.5	103	233.8
	22.35	7.52	112.0	108.8			136.5	89	
	26.82	9.19	108.6	105.4			136.5	74	
139.7	23.10	6.99	125.7	122.6	94.0	153.7	149.2	95	233.8
	25.33	7.72	124.3	121.1			149.2	86	
	29.80	9.17	121.4	118.2			149.2	73	
168.3	29.80	7.32	153.6	150.5	100.4	187.7	177.8	93	246.5
	35.76	8.94	150.4	147.2			177.8	77	
177.8	34.27	8.05	161.7	158.8	100.4	194.5	187.3	84	246.5
	38.74	9.19	159.4	156.2			187.3	74	
	43.21	10.36	157.1	153.9			187.3	66	
244.5	53.64	8.89	226.6	222.6	123.2	269.9	257.2	101	271.9
	59.60	10.03	224.4	220.4			257.2	90	
	64.82	11.05	222.4	218.4			257.2	82	
	70.03	11.99	220.5	216.5			257.2	76	
339.7	81.21	9.65	320.4	316.5	126.4	365.1	-	-	278.2
	90.89	10.92	317.9	313.9			-	-	
	101.32	12.19	315.3	311.4			-	-	
	107.28	13.06	313.6	309.7			-	-	