

Table 3 b

SUPERMAX-TS, SUPERMAX-TS2 Dimensions

Metric Unit

Pipe Body					Pin	Coupling			
Outside Diameter	Nominal Weight	Wall Thickness	Inside Diameter	Drift Diameter	Thread length	Standard Coupling OD	Special Clearance OD	Joint Efficiency	Length
in	lbs/ft	mm	mm	mm	mm	mm	mm	%	mm
60.3	4.60	4.83	50.7	48.3	69.3	73.0	68.6	114	163.7
	5.10	5.54	49.3	46.9			68.6	101	
	5.80	6.45	47.4	45.0			69.9	101	
73.0	6.40	5.51	62.0	59.6	70.9	88.9	82.6	112	167.0
	7.70	7.01	59.0	56.6			83.8	101	
	8.60	7.82	57.4	55.0			85.1	102	
88.9	7.70	5.49	77.9	74.8	77.3	108.0	97.8	103	179.7
	9.20	6.45	76.0	72.8			99.1	100	
	10.20	7.34	74.2	71.0			101.6	110	
108.0	9.50	5.74	90.1	86.9	77.3	120.7	111.8	109	179.7
	10.90	6.65	88.3	85.1			113.0	106	
	13.00	8.38	84.8	81.7			115.6	104	
	14.80	9.65	79.8	79.1			118.1	108	
114.3	10.50	5.69	102.9	99.7	83.6	127.0	124.5	109	192.4
	11.60	6.35	101.6	98.4			125.7	110	
	12.75	6.88	100.5	97.4			125.7	102	
	13.50	7.37	99.6	96.4			127.0	106	
	15.10	8.56	97.2	94.0			127.0	100	
127.0	16.02	7.52	112.0	108.8	94.0	141.3	136.5	89	227.4
	17.13	9.19	108.6	105.4			136.5	74	
139.7	18.24	6.99	125.7	122.6	94.03	153.7	149.2	95	227.4
	19.35	7.72	124.3	121.1			149.2	86	
	20.46	9.17	121.4	118.2			149.2	73	
168.3	21.57	7.32	153.6	150.5	100.38	187.7	177.8	93	240.1
	22.68	8.94	150.4	147.2			177.8	77	
177.8	23.79	8.05	161.7	158.8	100.38	194.5	187.3	84	240.1
	24.90	9.19	159.4	156.2			187.3	74	
	26.01	10.36	157.1	153.9			187.3	66	