

Table 4 b

FLUSHMAX Dimensions

Metric Unit

Pipe Body						Connection				
Outside Diameter	Nominal Weight	Actual Weight	Wall Thickness	Inside Diameter	Drift Diameter	Thread per inch	Make up loss	BOX OD	Pin ID	Joint Efficiency
mm	kg/m	kg/m	mm	mm	mm		mm	mm	mm	%
60.3	6.85	6.61	4.83	50.67	48.29	8	44.45	60.3	50.67	39.5
	7.60	7.48	5.54	49.25	46.86	8	44.45		49.25	46.6
	8.64	8.57	6.45	47.42	45.03	8	44.45		47.42	41.2
73.0	9.54	9.18	5.51	62.00	59.61	8	44.45	73.0	62.00	41.8
	11.47	11.41	7.01	59.00	56.62	8	44.45		59.00	42.2
	12.81	12.58	7.82	57.38	54.99	8	44.45		57.38	38.3
88.9	13.71	13.12	6.45	76.00	72.82	8	44.45	88.9	76.00	46.3
	15.20	14.77	7.34	74.22	71.04	8	44.45		74.22	43.7
108.0	14.16	13.57	5.74	90.12	86.94	8	44.45	108.0	90.12	47.5
	16.24	15.58	6.65	88.29	85.12	8	44.45		88.29	47.5