

Table 6b (rev.2)

FLUSHMAX-II and III Dimensions (Metric Unit)

	Pipe Body					Connection				
	OD	Nominal Weight	WT	ID	Drift	Thread per inch	Make up loss	BOX OD	Pin ID	Joint Efficiency
	mm	kg/m	mm	mm	mm		mm	mm	mm	%
FLUSHMAX-II	108.0	16.2	6.50	94.95	91.77	8	59.18	107.95	94.95	60.0
	114.3	15.6	5.69	102.92	99.75	8	59.74	114.30	102.92	60.0
	114.3	17.3	6.35	101.60	98.43	8	59.74	114.30	101.60	60.0
	114.3	19.0	6.88	100.53	97.36	8	59.74	114.30	100.53	60.0
	114.3	20.1	7.37	99.57	96.39	8	59.74	114.30	99.57	60.0
	127.0	22.4	7.52	111.96	108.79	8	62.23	127.00	111.96	60.0
	127.0	26.8	9.19	108.61	105.44	8	62.23	127.00	108.61	60.0
	139.7	23.1	6.99	125.73	122.56	8	62.23	139.70	125.73	60.0
	139.7	25.3	7.72	124.26	121.08	8	62.23	139.70	124.26	60.0
	139.7	29.8	9.17	121.36	118.19	8	62.23	139.70	121.36	60.0
	139.7	34.3	10.54	118.62	115.44	8	62.23	139.70	118.62	60.0
	168.3	29.8	7.32	153.64	150.47	8	62.23	168.28	153.64	60.0
	168.3	35.8	8.94	150.39	147.22	8	62.23	168.28	150.39	60.0
	177.8	34.3	8.05	161.70	158.52	8	63.50	177.80	161.70	60.0
	177.8	38.7	9.19	159.41	156.24	8	63.50	177.80	159.41	60.0
177.8	43.2	10.36	157.07	153.90	8	76.20	177.80	157.07	60.0	
177.8	47.7	11.51	154.79	151.61	8	76.20	177.80	154.79	60.0	
FLUSHMAX-III	193.7	44.3	9.53	174.63	171.45	5	77.22	193.68	174.63	60.0
	193.7	50.2	10.92	171.83	168.66	5	80.26	193.68	171.83	60.0
	193.7	53.3	11.81	170.05	166.88	5	82.30	193.68	170.05	60.0
	193.7	58.1	12.70	168.28	165.10	5	84.33	193.68	168.28	60.0
	219.1	47.7	8.94	201.19	198.02	5	75.95	219.08	201.19	60.0
	219.1	53.6	10.16	198.76	195.58	5	78.49	219.08	198.76	60.0
	244.5	53.6	8.94	226.59	222.63	5	75.95	244.48	226.59	60.0
	244.5	59.6	10.03	224.41	220.45	5	78.23	244.48	224.41	60.0
	244.5	64.8	11.05	222.38	218.41	5	80.52	244.48	222.38	60.0
	273.1	60.3	8.89	255.27	251.31	5	75.95	273.05	255.27	60.0
	273.1	67.8	10.16	252.73	248.77	5	78.49	273.05	252.73	60.0
	273.1	76.0	11.43	250.19	246.23	5	81.53	273.05	250.19	60.0

* Note) FLUSHMAX-II and III are not interchangeable among same OD and different unit weight sizes.